



Ordinary Locations

Immersion separator

- **Vacuum assisted sanding kit system for the automotive/ aerospace industries**
- **ETL® Certified for ordinary areas/locations**
- HEPA Filter - Included with an efficiency of 99.995% on 0.3 micron. Tested: IEST RP-CC001.3. H14 by MPPS method as per EN 1822.
- Wye Connector included (part# 501503)
- Coalescing Filter Element (CFE)
- Detachable oil/water tank for easy emptying of recovered materials
- **Fully integrated automatic On/Off switch** allows the electrically operated vacuum cleaner to be controlled by a pneumatic hand tool
- Included: Two (2) Suction/Air hoses, static conductive crushproof, 20' (15' x 1.25" + 5' x 1") (part# 303190)
- Arslan Automotive has a large selection of optional dustless hand tools



Specifications for immersion separator:

	Unit	AS-400/85L (OL) SK HEPA
Part#		112420A-ARS
Filtration System		Immersion Separator
Dry Recovery	gal	1.3 gallons of dust into 7.9 gallons of neutralizing liquid

Performance specifications:

	Unit	AS-400/85L (OL) SK HEPA
Vacuum Pressure	Inches H2O	107
Air Flow	CFM	128
Phase		Single
Horse Power	HP	1.6
Amperage	A	10.5
Wattage	W	1260
Hertz	Hz	60
Voltage	V	120
Noise Level	dB	63
Weight	lbs	220
Dimensions	Inches	24 x 41 x 70(high)
Plug		Included (ordinary location)

Coalescing Filter Element

The Coalescing filter element is used for the removal of solid particles, water and oil aerosols.
