

VACUUM MODEL 50-DAV-5 AIR OPERATED DUSTLESS SANDING VACUUM CLEANER

- > LOW AIR CONSUMPTION
- > STAINLESS STEEL & ALUMINUM
- ➤ HEPA^{Plus*} FILTRATION 99.995 % @ 0.2 MICRON
- > STATIC DISSIPATING ESD SAFE
- > 3 YEAR WARRANTY

Explosion Proof / Dust Ignition Proof Air-Operated Pneumatic DUSTLESS SANDING VACUUM CLEANER



Arslan Dustless Sanding Vacuums are specifically designed to safely vacuum the hazardous dust generated during surface preparation, coating removal and body repair in the automotive industry. Arslan explosion proof/dust ignition proof vacuums are designed to safely vacuum explosive, flammable, combustible conductive dusts. These explosion proof vacuums comply with NFPA 484 guidelines and are an effective tool for good housekeeping practise as per OSHA. Compressed Air-Operated Vacuums do not have any electrical components that can overheat and be a source of ignition. Our explosion proof/dust ignition proof vacuums are completely grounded and static dissipating because they are built entirely with non-sparking metals and do not have any painted components so there is no risk of fire or explosion from a spark or static build up.

II 2 GD c IIC T6 (85°C)

Class I, Division 1, Groups A, B, C, and D T6 and Class II, Division 1, Groups E, F, G Hazardous Locations as defined in the National Electric Code (NEC) and NFPA 70 EPL Db and EPL Gb (Equipment Protection Level)



Features:

- Low Air Consumption
- Stainless steel construction makes it a solid unit that is easy to clean
- Static dissipating ESD safe
- Complete with static dissipating suction hose

Filtration System:

- Washable Conductive ESD safe filters
- **HEPA**^{Plus*} Filtration with an efficiency of 99.995% @ 0.2 micron

Specifications:

- Dry Collection Only
- Collection Capacity 5 gallon

Dimensions:

• 24" x 24" x 46" weight : 120 lbs

Air requirements:

• 8 CFM Input Air Flow

• 60 PSI Input Pressure (minimum)

• ½" Air Line Hose

Included:

- Static Dissipating Suction w/ Air Supply hose assembly 20'
- Static Dissipating Airline Hose Connection

